



SPECIFICATIONS

FourStroke: 150 hp



HP / kW	150 / 110
Engine type	8-valve single overhead cam (SOHC) Inline 4
Displacement (L)	3.0
Full throttle RPM	5000-5800
Air induction	Performance-Tuned Scroll Intake Manifold
Fuel induction system	Computer Controlled Multi-Port Electronic Fuel Injection (EFI)
Alternator amp / Watt	60 amp / 756 watt (Belt-Driven)
Recommended fuel	Unleaded 90RON minimum
Recommended oil	Mercury FourStroke Oil 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes
Starting	Electric (turn-key) Smart Start Electric
Controls	Mechanical throttle & shift
Steering	Big Tiller Compatible Dual cable mechanical Electro-Hydraulic Power Steering Optional on Duals Hydraulic power steering
Shaft length	20" / 508 mm 25" / 635 mm
Gearcase ratio	1.92:1
Dry weight *Lightest model available	206 kg
Bore and stroke	4.0 x 3.6" / 102 x 92 mm
Ignition	SmartCraft ECM 70 Digital Inductive
Fuel system	Electronic Fuel Injection (EFI)

Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	Standard
Trim system	Power Tilt Power Trim
Exhaust system	Through prop
Counter Rotation	Available
Color	Phantom Black
Lubrication system	Wet sump
Oil Capacity	6.3 qts / 6.0l
Maximum Trim Range	22° (-6° to 16°)
Maximum Tilt Range	73° (-6° to 67°)



SPECIFICATIONS

OptiMax® & Pro XS™: Pro XS 150-200 hp



HP / kW	150 / 110
Engine type	V-6
Displacement (L)	2.5
Full throttle RPM	5250-5750
Alternator amp / Watt	60 amp / 756 watt (Belt-Driven)
Recommended fuel	Unleaded 90RON minimum
Recommended oil	Mercury OptiMax/DFI Outboard Oil
Engine protection operator warning system	Low oil level Over-rev Overheat SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes
Starting	Electric (turn-key)
Steering	Big Tiller Compatible Dual cable mechanical Hydraulic power steering
Shaft length	20" / 508 mm 25" / 635 mm
Gearcase ratio	1.87:1
Dry weight *Lightest model available	195 kg
CARB star rating	3
Bore and stroke	3.50 x 2.65" / 89 x 67 mm
Ignition	PCM Digital Inductive
Fuel system	2-stage Direct Fuel Injection (DFI)
Cooling system	Water-cooled with thermostat & pressure-controlled
Gear shift	F-N-R
Gearcase options	Standard

Trim system	Power Trim
Exhaust system	Through prop
Shallow water trim range (degrees)	20
Color	Phantom Black
